

Divers' Hot Water. Com



The D.H.H. 690A Standard Diver's HotWater Heaters are a solid, sturdy piece of offshore equipment designed out of necessity for simplicity and dependability to keep your divers warm so they may deliver a maximum amount of work safely and comfortably.

Accident-free and Warm Divers are Consistently More Productive.



**The D.H.H. 690A Standard
Diver's HotWater Heaters
are available for Purchase
and Rental.**

***Custom size units
available**

SIMPLICITY & DEPENDABILITY

Designed to be operated by your Diver Tender. 120V AC 15 AMP's. Water is picked up by a heavily encased all 316 Stainless Submersible Pump which pushes seawater through Heat Exchangers (which are suspended in fresh water) to the diver. Water temp is controlled by a 2° aquastat-backed up by another hi-temp cut off aquastat. An emergency hand operated mix valve, backs up this system.

A Beckett Oil Gun explodes diesel fuel in the underwater fire box vented to the atmosphere via boiler tubes and heat dissipator swirls in the fresh water side, heating the medium, which in turn proportionally heat the saltwater as it passes through the heat exchangers to the diver. We thus eliminate pump priming – mix valves – high voltage requirements, circulating pumps & complex electrical components. This unit functions with both doors closed to eliminate salt water spray.

Gary Herman Companies, LLC **Db a Alpha Rentals**

4706 Curtis Lane
New Iberia, La. 70560

Phone: 337-367-2880
Fax: 337-606-9890
Email: gary@hermanrentals.com

SPECIFICATIONS

MODEL A.....DHH 690A

Height..... 67"
Width..... 41"
Length 48"
Weight Empty 1982lbs
Weight Full 3100lbs
Fuel Capacity (diesel) 59 gallons
Fresh Water Capacity..... 165 gallons
Hot Water Reserve..... 25-30 minutes

Rate cap. out-put 690000 BTUH Continuous
Fire Tube Size 2 ½" X 24"
Oil Gun..... Beckett 3.0" to 5 ½" GPH Nozzle
Oil Pump Sunstrand
Electrical Requirements 120 V.A.C. 15 AMP
Nozzle Size..... 3.0 – 5.5 G.P.H.
GFI.....(customer supplied) 15 AMP

HIGH QUALITY CONSTRUCTION

- Water Tight Plugs for Component Replacement
- Heavy Duty Skids and Lifting Pads
- 316 Stainless Steel Submersible Pump
- Honeywell Aquastats
- Galvanized Dipped
- Beckett Oil Gun
- Designed for Complete Disassembly and Re-assembly for Cleaning and Maintenance